

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification 7 :</b> <b>H04Q 7/32</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/54530</b> <b>(43) International Publication Date:</b> 14 September 2000 (14.09.00)
<b>(21) International Application Number:</b> PCT/US00/06552 <b>(22) International Filing Date:</b> 13 March 2000 (13.03.00) <b>(30) Priority Data:</b> 09/267,824      12 March 1999 (12.03.99)      US <b>(71) Applicant:</b> QUALCOMM INCORPORATED [US/US]; 5775 Morhouse Drive, San Diego, CA 92121 (US). <b>(72) Inventors:</b> HUTCHISON, James, A., IV; 2013 Cardinal Drive, San Diego, CA 92123 (US). LEKVEN, Eric, J.; 7961 Via Orilla, Carlsbad, CA 92009 (US). <b>(74) Agents:</b> WADSWORTH, Philip, R. et al.; Qualcomm Incorporated, 5775 Morehouse Drive, San Diego, CA 92121 (US).		<b>(81) Designated States:</b> AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
<b>(54) Title:</b> SYSTEM AND METHOD FOR INDEPENDENTLY DOWNLOADING FEATURES INTO A SET OF STORAGE LOCATIONS IN A WIRELESS COMMUNICATION DEVICE		
<b>(57) Abstract</b> <p>A system and method (100) for independently downloading a main program and optional features (124) into a set of storage locations (114) of a wireless communication device (102) uses a memory (123) to store the main program and a set of selected optional features (124). An identification element (160) associated with one in the set of selected optional features (162) enables the main program (134) to interact with the one in the set of selected optional features (124-130). A programmer (not shown) programs the selected optional feature programs (124-130) into the memory (116) by locating a storage location in the memory (116). An indicator indicates when the set of selected optional features has been stored in the memory. The memory can further contain a linking element and a pointer (162-166) to identify storage locations in the memory. The invention allows the set of selected optional features to be stored after the main program is stored in the memory.</p>		

Best Available Copy

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

WO 00/54530

PCT/US00/06552

1

## SYSTEM AND METHOD FOR INDEPENDENTLY DOWNLOADING FEATURES INTO A SET OF STORAGE LOCATIONS IN A WIRELESS COMMUNICATION DEVICE

5

### FIELD OF THE INVENTION

The present invention is related generally to wireless communication devices, and more particularly, to a system and method for independently downloading features into a memory location of a wireless communication  
10 device.

### BACKGROUND OF THE INVENTION

Modern wireless communication devices, such as cellular telephones, are very popular because they are convenient to use and provide many features and options that are difficult to implement on conventional telephones. For  
15 example, a wireless communication device can be programmed and customized with the specific dialing plans and dialing patterns for a particular country. In this fashion, wireless communication devices can be mass-produced for export to a foreign country and ready to use immediately without additional programming. For the United States, a wireless communication device can be  
20 programmed to accommodate 10-digit telephone numbers of the North American Numbering Plan and the "star" codes used to activate numerous options available in the telephone carrier's system.

A wireless communication device can be further programmed for operation with data encryption schemes, for operation with foreign language  
25 text, and to allow its user to play computerized wireless games. These features can be implemented in various combinations in each wireless communication device to provide the user with several customized features.

The optional features discussed above are pre-programmed into the wireless communication device by its manufacturer during the production  
30 process. The data and executable code/instructions that are associated with and that operate each of these optional features are combined with the standard data and executable code/instructions (i.e., the main program) that control the

WO 00/54530

PCT/US00/06552

2

operation of the wireless communication device. The combined program is then written into an electronically erasable read-only-memory (EEPROM) of the wireless communication device. That is, the optional features and the main program are both written or downloaded into the EEPROM as a single program  
5 and at the same time. Other forms of writeable non-volatile storage may also be used (e.g., FERAM, battery-backed RAM, OPT RAM, etc.).

There are several significant disadvantages to utilizing a single download. First, because the main program and the optional features need to be downloaded as a single program, the manufacturer has to predetermine  
10 which optional features will be required by the wireless communication device, and then assimilate the optional features into the main program. This method is undesirable because it is often difficult to predict which optional features will be requested by a given customer, and it is an inefficient use of memory space to account for every optional feature by combining all possible optional features  
15 with the main program.

Second, because the optional features and the main program are combined and downloaded together, additional optional features cannot be added to the EEPROM after the initial download is made. If the manufacturer desires to add additional optional features to the wireless communication  
20 device, then the entire EEPROM needs to be erased or replaced, with the updated combination of the optional features and the main program being subsequently downloaded into a new blank EEPROM. Also, because the optional features are bound to the main program as a single combined program, portions of the main program itself may need to be updated each time  
25 the manufacturer simply wants to add a single optional feature. Obviously, this updating has to be done before the combined program is downloaded into the EEPROM, because conventional systems cannot update the combined program once it is downloaded.

Third, the large block of information resulting from combining the  
30 optional features with the main program may inherently make downloading more difficult. A single continuous storage block of the EEPROM may need to

WO 00/54530

PCT/US00/06552

3

be pre-allocated to accommodate the entire block of downloaded information. It is possible that the block of downloaded information cannot be separated into portions which are then stored at scattered storage blocks of the EEPROM. For instance, it may be desirable in some instances to write the main program into one storage block of the EEPROM and then write the optional features into  
5 wherever other scattered storage blocks of the EEPROM are available.

Accordingly, there exists a need to be able to customize a wireless communication device with optional features in a manner such that the optional features can be downloaded into the EEPROM independent of the  
10 downloading of the main program. The present invention provides solutions to the problems described above as will be apparent from the following detailed description and accompanying figures.

### SUMMARY OF THE INVENTION

15 The present invention is embodied in a system and method for downloading optional features into a memory of a wireless communication device. In an exemplary embodiment, the wireless communication device comprises the memory to store a main program to control operation of the wireless communication device. A set of selectable optional features is  
20 programmable into the memory independently of the main program. The main program uses identification elements associated with the set, or sets, of selectable optional features to interact with the selected set of selectable optional features.

An exemplary embodiment further includes a linking element to also  
25 associate the main program to the set of selectable optional features, the linking element being inactive until the set of selectable optional features is programmed into the memory. The linking element can be a portion of the main program and can include a plurality of pointers to identify a plurality of corresponding storage locations in the memory. The main program can also  
30 include a searching program to search the memory for a storage location corresponding to the set of selectable optional features, the storage location

WO 00/54530

PCT/US00/06552

4

having an indicator to indicate when the set of selectable optional features is stored in the storage location.

The linking element can also include a pointer identifying a secondary linking element, the secondary linking element having a plurality of pointers to identify a corresponding plurality of storage locations in the memory. In  
5 exemplary embodiments of the invention, the set of selectable optional features can also include the secondary linking element or a pointer to identify a storage location in the memory.

A programmer and a port coupled to the memory receives the set of  
10 selectable optional features. The programmer sends the set of selectable optional features to the port for storage in the programmable memory independent of a storing of the main program. The set of selectable optional features could include features such as a dialing plan system, encryption system, browser system, or a language system, or diagnostic extensions and  
15 alterations, system management, selection and presentation extensions and alterations, and audio handling extensions and alterations, productivity tools, and games.

## BRIEF DESCRIPTION OF THE DRAWINGS

20 In the figures, like reference numerals refer to like parts throughout the various views unless otherwise indicated.

FIG. 1 is a functional block diagram of an exemplary embodiment of the wireless communication system of the present invention.

FIG. 2 is a schematic of a programmable memory of the embodiment  
25 shown in FIG. 1.

FIG. 3 is a link table for the programmable memory shown in FIG. 2.

FIG. 4 is a flowchart illustrating a downloading operation for the embodiments shown in FIGS. 1-3.

WO 00/54530

PCT/US00/06552

5

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention is embodied in a system 100 illustrated in the  
5 functional block diagram of FIG. 1. The system 100 includes a wireless  
communication device 101, which may be embodied in a cellular telephone.  
The system 100 includes a housing 102 that contains a transmitter 104 and a  
receiver 106 to allow transmission and reception of data, such as audio  
communications, between the system 100 and a remote location, such as a cell  
10 site controller (not shown). The transmitter 104 and the receiver 106 may be  
combined into a transceiver 108. An antenna 110 is attached to the housing 102  
and is electrically coupled to the transceiver 108. The operation of the  
transmitter 104, receiver 106, and antenna 110 is well known in the art and need  
not be described herein. Although described herein as a cellular telephone, the  
15 principles of the present invention are applicable to a variety of wireless  
communication devices including, but not limited to, cellular/PCS, radio  
telephone, and the like. Accordingly, the present invention is not limited by the  
specific form of wireless communication device.

The wireless communication device 101 has a central processing unit  
20 (CPU) 112, which controls operation of system 100. The CPU 112 may perform  
all the tasks involved in the operation of the system 100, or only a portion of  
them, where the remaining tasks are delegated to other processing units (not  
shown) included in the system 100.

The wireless communication device 101 includes one or more memory  
25 units, which may be a random-access-memory (RAM) 114 and a programmable  
memory 116, such as an electronically erasable programmable read-only-  
memory (EEPROM). The RAM 114 could include non-volatile RAM to store  
information that must be present upon powering the wireless communication  
device 101. As is known in the art, portions of the RAM 114 can be used as  
30 shadow read-only-memory (ROM) to store information, such as data and  
executable code/instructions, normally stored in the programmable memory

WO 00/54530

PCT/US00/06552

6

116 or in a standard ROM (not shown). Additionally, while FIG. 1 makes a distinction between the programmable memory 116 and the RAM 114, one skilled in the art would appreciate that the RAM 114 is also a type of "programmable" memory. The CPU 112 processes the information stored in the RAM 114 or in the programmable memory 116 to operate the wireless communication device 101.

The wireless communication device 101 further includes an input/output port 118 to receive a set of features 123, sometimes referred to as a "bundle," from a programmer 122 located outside of the housing 102. The programmer 122 is a system of hardware and software that enables features to be downloaded into the wireless communication device 101. The system 100 can also have a downloader 115 in the RAM 114 to receive features from the programmer 122 and to write the received features into the appropriate memory location. As such, the downloader 115 acts as an intermediate downloading program between the programmer 122 and the programmable memory 116 or the RAM 114.

For purposes of present invention, the term "features" used throughout this description is understood to include data, executable software code, and any of their accompanying information, such as identification (ID) codes and variables, that are written into the programmable memory 116 or into the RAM 114 by the programmer 122 or by the downloader 115. The set 123 comprises a collection of individual optional features associated with any number of individual optional features 124, 126, 128, and 130. For example, FEATURE 1, shown as 124 in FIG. 1, could correspond to data for a dialing plan of the country of India. The programmer 122 writes the optional features contained in the set 123 into the programmable memory 116 or into the RAM 114 as individual optional features (e.g., FEATURE 1) or as a "bundle" of individual optional features (e.g., FEATURE 1, FEATURE 3, and FEATURE 4). It should be noted that an individual optional feature itself also can be referred to as a "bundle," since any given individual optional feature is a "bundle" of data and



WO 00/54530

PCT/US00/06552

7

executable code. Therefore, the terms "bundle" and "feature" are used interchangeably throughout this description.

It is to be appreciated that the set 123 could reside within the programmer 122 or it could be accessible to the programmer 122 via a first communication link 132. Also, while only one set 123 is shown in FIG. 1, it is to be appreciated that there may be numerous other sets accessible to the programmer 122. One of these other sets could include the main program that the wireless communication device 101 needs in order to function.

A second communication link 133 couples the programmer 122 to the input/output port 118 to allow the set 123 to be written or downloaded into the programmable memory 116 or into the RAM 114. The various components within the housing 102 are coupled together by a bus system 120, which may include a power bus, control bus, and status signal bus in addition to a data bus. However, for the sake of clarity, the various buses are illustrated in FIG. 1 as the bus system 120. In addition, although not described herein or shown in FIG. 1 because they are not relevant to what is considered to be the present invention, one skilled in the art would understand that the wireless communication device 101 has additional elements, such as a keypad, battery, and display.

As described above, conventional wireless communication systems require the combination of the optional features and the main program, with the combined program being programmed into an EEPROM. The present invention allows the downloading process for one or more optional features to be separated from the downloading process of the main program. FIGS. 2-4 illustrate how this can be done.

FIG. 2 is a schematic of the programmable memory 116 of an exemplary embodiment of the present invention. The main program is written into a storage block (memory locations) 134 of the programmable memory 116. The bundles FEATURE 1, FEATURE 2, and FEATURE 3 belonging to the set 123 of FIG. 1 and shown as 124, 126 and 128 respectively, are written into other storage blocks of the programmable memory 116. Each bundle, such as FEATURE 1,

WO 00/54530

PCT/US00/06552

8

further includes an identification (ID) 136, one or more pointers 138-140, and a flag 142. An empty storage block 152 allows additional future bundles to be written into the programmable memory 116.

As mentioned above, the FEATURE 1 bundle can contain both data and  
5 executable code, and is schematically shown as the storage block 124 in the programmable memory 116. The ID 136 could include information such as a byte size of the FEATURE 1 bundle, its memory address, and a code identifying what type of bundle it is (e.g., a dialing plan).

Pointers are known to those skilled in the art, and are generally variables  
10 that contain a memory address of the programmable memory 116 or the RAM 114 where a particular set of data or executable subroutine associated with the FEATURE 1 bundle can be accessed. The access location of a bundle is sometimes referred to as an "entry point." Each bundle can include multiple pointers to any number of entry points of other bundles. For instance,  
15 POINTER 1, shown as 138, can point to a memory location in the storage block 134 that initiates activation of the FEATURE 1 bundle. As another example, POINTER 2, shown as 139, may point to another bundle that needs to run concurrently with the FEATURE 1 bundle, thereby dynamically linking the FEATURE 1 bundle with that other bundle. In this fashion, the pointers are  
20 able to dynamically link groups of programs or portions of programs with each other, eliminating the need to combine all of the programs into a single program or memory location.

The flag 142 provides indication data, such as if the particular bundle 124 is valid or successfully loaded into the EEPROM 116 or if a memory location is  
25 occupied by a bundle. Although FIG. 2 shows the ID 136, pointers 138-140, and the flag 142 as being segregated from the storage block 124, it is to be appreciated that this information can be integrated within the storage block 124 as well. Additionally, while FIG. 2 shows the optional features being located in storage blocks 124, 126, and 128 of the programmable memory 116, one skilled  
30 in the art would understand that portions of these features may be written into the non-volatile portion of the RAM 114 (see FIG. 1). If this is done, the

WO 00/54530

PCT/US00/06552

9

information in the non-volatile RAM 114 would be linked to and accessible to the programmable memory 116 by appropriate pointers.

Another example of an optional feature and its pointers is a data encryption scheme, shown as the FEATURE 2 bundle in the storage block 126.

5 The data and executable code to encrypt information are stored in the storage block 126. This program has an ID 144 to indicate that it is an encryption bundle and a flag 150 to indicate that the storage block 126 is loaded. Pointers 146 and 148 point to memory locations (i.e., entry points) where public and/or private decryption keys, respectively, are stored. Keys and support functions  
10 can also be stored externally to the feature and passed to the bundle by the caller that uses the feature.

In an exemplary embodiment of the invention, the main program in storage block 134 includes routines to search through the programmable memory 116 to try to find any of the optional features 124, 126, and 128. These  
15 routines use known optimization techniques to minimize the time required to search for any given optional feature. Once an optional feature is located, other routines in the main program interact with the optional feature to activate the optional feature. Accordingly, there is no requirement for the main program to initially know the specific memory location of an optional feature. The main  
20 program need only have the capability of knowing that an optional feature can be downloaded and to search the programmable memory 116 for the optional feature.

In another exemplary embodiment of the invention, a link table 160, shown in FIG. 3, may be alternatively or additionally included in the  
25 programmable memory 116 or in the non-volatile portion of the RAM 114. The link table 160 contains one or more pointers 162, 164, and 166 to conveniently locate and dynamically link entry points associated with the respective bundles 124, 126, and 128. That is, instead of the main program of the wireless communication device 101 or the programmer 122 having to search through the  
30 entire programmable memory 116 for a particular bundle, the main program or

WO 00/54530

PCT/US00/06552

10

the programmer 122 can look to the link table 160 to immediately obtain the location of a particular bundle.

The link table 160 can include a pointer that points to another link table, which in turn can point to additional bundles or link tables. In this fashion, many levels of bundles in the system 100 can be linked together by pointers and link tables. Some exemplary embodiments of the link table 160 may also have a location 168 to allow additional pointers (pointing to another link table or to a bundle) to be added to the link table 160 as new bundles and link tables are written into the programmable memory 116. Although not shown in FIG. 3, the link table 160 can also have a flag or ID associated with each pointer 162, 164, and 166. For instance, the pointer 162 can have a flag to indicate when the memory location it is pointing to is loaded with a bundle.

The main program in the storage block 134 contains a pointer (not shown) to the link table 160 to provide the appropriate operating interrelationship and linking between the main program and the link table 160. Alternatively, the link table 160 may be incorporated within the main program itself. Further, unused storage blocks of the programmable memory 116 can be pre-allocated for future downloads of optional features and individually addressed and vectored via pointers in the link table 160. In other exemplary embodiments that do not utilize a link table 160, the main program can contain an optional feature list or subroutines to activate each optional feature. The main program can then identify and activate a later-downloaded optional feature by using conventional function call commands.

In an exemplary embodiment of the invention that utilizes a link table 160, the main program and the link table 160 are loaded together as a combined program during the initial downloading process. The optional features need not be downloaded at this time, but the manufacturer can include pointers in the link table 160, such as encryption and dialing plan pointers, in anticipation that the bundles for these features will be subsequently loaded in the future. That is, by loading the link table 160 having predetermined pointers with the main program, the main program has a mechanism for knowing that new

WO 00/54530

PCT/US00/06552

11

bundles can be added, what the bundles are, where the bundles will be located, and can then dynamically link to the bundles. As will be explained below, the link table 160 is in an inactive default stage when it is first loaded into the wireless communication device 101. The link table remains in the default stage  
5 until initialized by the programmer 122 when a bundle is to be downloaded.

In summary, an exemplary embodiment of the invention allows optional features to be downloaded separately from the main program. Even though the optional features and the main program are downloaded separately, they can nevertheless interact with and access each other through the use of pointers.  
10 While the present invention still allows the main program to be combined with optional features in a single download, as will be described next, the present invention removes the requirement of having to write the main program into the programmable memory 116 concurrently with the optional features and the dynamic loading feature allows optional features to be added or altered  
15 without having to reprogram the entire programmable memory 116. For example, the programmable memory 116 may initially be programmed with a version of the FEATURE 2 (i.e., encryption) bundle 126 for domestic use in the United States. At a subsequent time, it may be desirable to replace the domestic version of the encryption with a version of encryption suitable for exportation.  
20 The dynamic loading of system 100 allows the user to reprogram only the FEATURE 2 bundle 126 as well as pointers, if necessary, without the necessity of reprogramming the entire programmable memory 116.

FIG. 4 shows a flowchart illustrating the downloading process for the programmable memory 116 shown in FIG. 2. In embodiments that utilize the  
25 downloader 115, it is assumed that the downloader 115 (see FIG. 1) is already in place in the RAM 114. The downloader 115 interacts with the programmer 122 to program the programmable memory 116. The operation of the programmer 122 and the downloader 115 is well known in the art and need not be described in detail herein.

30 At step 170 of an exemplary embodiment of the invention, the main program associated with the basic operation of the wireless communication

WO 00/54530

PCT/US00/06552

12

device 101 is downloaded/written first by the programmer 122 into the storage block 134 of the programmable memory 116. In embodiments where the link table 160 is to be used, the link table 160 having predetermined pointers but in an inactive default stage, is also loaded along with the main program during  
5 step 170. The link table 160 need not be necessarily written into the storage block 134. If needed, the main program in the storage block 134 can contain a pointer linking to the memory location of the link table 160.

At step 172, if a manufacturer does not wish to add any optional features to the wireless communication device 101, then the programmer 122 completes  
10 the downloading process at step 182, and the wireless communication device 101 is ready for distribution to consumers. The link table 160, if there is one downloaded, remains in its inactive state.

However, if the optional features associated with the bundles 124, 126, 128, and 130 in the set 123 are to be added, then at step 174, the programmer 122  
15 looks for an available storage block in the programmable memory 116 to download the bundles. As previously described above, it is not required for the bundles to be downloaded into pre-assigned storage blocks. The bundles can be downloaded into any available storage block because main program in storage block 134 has search routines that search through the programmable  
20 memory 116 to locate the bundle after it has been downloaded. It should be noted that prior to step 174, the manufacturer determines whether to download the bundles 124, 126, 128, and 130 into the programmable memory 116 as individual bundles or as a combination of several bundles forming a large bundle. The bundling process is performed offline, prior to step 174, by the  
25 programmer 122.

Alternatively at step 174 for embodiments that utilize the link table 160, the programmer 122 initializes the inactive link table 160, reads the link table 160 to determine if a pointer in the link table 160 has designated a storage block for the bundle, and then goes to that storage block in the programmable  
30 memory 116 to download the bundle. The link table 160 remains in an active state once initialized by the programmer 122.

WO 00/54530

PCT/US00/06552

13

At step 176, the programmer 122 or the downloader 115 downloads the bundle into a storage block in the programmable memory 116. At step 178, the applicable flags 142 or 150 (see FIG. 2) are set by the programmer 122 to indicate that the bundle has been successfully downloaded and is functional.

5 Also at step 178, for embodiments that utilize the link table 160, flags in the appropriate pointers 162, 164, or 166 of the link table 160 may also be set by the programmer 122 to indicate which memory blocks have been loaded. During step 178, the programmer 122 can also update the link table 160 at location 168, if necessary, to add new pointers to storage blocks where additional bundles

10 may be loaded in succeeding downloading procedures.

While steps 176 and 178 above have been described broadly as a loading of a "bundle" into the programmable memory 116, it is understood that this "bundle" can be an optional feature, another link table, a set of pointers, alterations to the main program, or a combination of these items. Accordingly,

15 the present invention allows the manufacturer to build upon and update the existing contents of the programmable memory 116 in a variety of ways and is not limited by the type of bundle being downloaded into the programmable memory 116.

After the bundle is downloaded into the programmable memory 116 and

20 if no additional bundles will be added at step 180, then the downloading process is completed at step 182. If more bundles need to be added, then the process described above is repeated, starting at step 174.

In summary, the downloading process shown in the flowchart of FIG. 4 allows bundles of optional features to be added to the programmable memory

25 116 independently of the main program. In this fashion, the wireless communication device 101 can be customized independent of the initial programming.

From the foregoing it will be appreciated that, although specific embodiments of the invention have been described herein for purposes of

30 illustration, various modifications may be made without deviating from the spirit and scope of the invention. For example, while the figures for the

WO 00/54530

PCT/US00/06552

14

- embodiments described above show the bundles being written into the programmable memory 116, a portion of a bundle, an entire bundle, or all of the bundles may be stored in the non-volatile portion of the RAM 114. These bundles are dynamically linked to each other or to the main program
- 5 by pointers. Accordingly, the invention is not limited except as by the appended claims, the interpretation of which are to be made in accordance with established doctrines of claim interpretation.

What is claimed is:



WO 00/54530

PCT/US00/06552

15

## CLAIMS

1. A wireless communication device comprising:  
2 a memory;  
a main program stored in the memory to control operation of the  
4 wireless communication device;  
a set of selectable optional features programmable into the memory  
6 independent of the main program; and  
an identification associated with at least one of the set of independently  
8 programmed selectable optional features, the main program using the  
identification to interact with the at least one of the set of independently  
10 programmed selectable optional features.

2. The device of claim 1, further comprising a linking element, the  
2 linking element remaining inactive until the set of the selectable optional  
features is programmed into the memory.

3. The device of claim 2 wherein the linking element is a portion of  
2 the main program and includes a plurality of pointers to identify a plurality of  
corresponding storage locations in the memory, the plurality of corresponding  
4 storage locations storing a corresponding selectable optional feature in the set.

4. The device of claim 1 wherein the main program includes a  
2 searching program to search the memory for a storage location corresponding  
to the one of the set of selectable optional features, the storage location having  
4 an indicator to indicate when the one in the set of selectable optional features is  
stored in the storage location.

5. The device of claim 1 wherein the set of the selectable optional  
2 features includes a pointer to identify a storage location where the one of the set  
of the selectable optional features is stored.

WO 00/54530

PCT/US00/06552

16

6. The device of claim 1 wherein the set of the selectable optional features includes a linking element, the linking element having a pointer to identify a storage location of the memory storing the one of the set of the selectable optional features, the main program utilizing the linking element to interact with the one in the set of the selectable optional features identified by the pointer.

7. The device of claim 1 wherein the at least one of the set of the selectable optional features comprises a selected one of a dialing plan system, an encryption system, a browser system, or a language system.

8. A programming system for a wireless communication device comprising:

a wireless communication device having a programmable memory, the programmable memory having a first storage location to store a main program associated with operation of the wireless communication device and a second storage location different from the first storage location;

a port coupled to the programmable memory to receive a set of selectable optional features for the wireless communication device;

a programmer coupled to the port to send the set of selectable optional features to the port for storage in the second storage location, the programmer storing the set of selectable optional features in the second storage location independently of a storing of the main program in the first storage location; and

a linking element to associate the main program with the set of selectable optional features.

9. The system of claim 8 wherein the linking element is stored in the first storage location with the main program, the linking element having an indicator set by the programmer to indicate when the set of selectable optional features are stored in the second storage location.

WO 00/54530

PCT/US00/06552

17

10. The system of claim 9 wherein the linking element includes a  
2 pointer to direct the programmer where to store the set of selectable optional  
features in the programmable memory.

11. The system of claim 8 wherein the linking element is stored in a  
2 storage location of the programmable memory different from the first storage  
location.

12. The system of claim 8 wherein the linking element includes a  
2 pointer identifying a secondary linking element, the secondary linking element  
having a plurality of pointers to identify memory locations in the  
4 programmable memory.

13. The system of claim 8 wherein the set of selectable optional  
2 features includes a pointer to identify a memory location in the programmable  
memory.

14. The system of claim 8 wherein the set of selectable optional  
2 features includes a secondary linking element, the secondary linking element  
having a plurality of pointers to identify a plurality of corresponding memory  
4 locations in the programmable memory.

15. The system of claim 8 wherein the set of selectable optional  
2 features includes a first indicator to indicate when one of the set of selectable  
optional features is stored in the second storage location and a second indicator  
4 to identify a memory location in the second storage location where the one of  
the set of selectable optional features is stored, a size of the memory location, or  
6 a type of the one of the set of selectable optional features.

16. The system of claim 8 wherein the linking element remains  
2 inactive until activated by the programmer, the programmer activating the  
linking element when the programmer sends the set of selectable optional

WO 00/54530

PCT/US00/06552

18

4 features for storage in the second storage location, the linking element having  
an indicator set by the programmer to indicate when the set of selectable  
6 optional features is stored in the second storage location.

17. A wireless communication device comprising:

2 a first storage location storing a main program associated with operation  
of the wireless communication device;  
4 a second storage location programmable to store a set of selectable  
optional features independently from the main program;  
6 a linking element to associate the main program with the set of selectable  
optional features, the linking element associating the set of selectable optional  
8 features with the main program when the second storage location is  
programmed to store the set of selectable optional features; and  
10 an indicator to indicate when the set of selectable optional features is  
stored in the second storage location.

18. The device of claim 17 wherein the linking element includes a  
2 plurality of pointers to identify corresponding empty locations in the second  
storage location, the set of selectable optional features being stored in the empty  
4 locations identified by the plurality of pointers, the empty locations having an  
indicator to indicate when the set of selectable optional features is stored in the  
6 empty locations.

19. The device of claim 17 wherein the main program includes a  
2 searching program, the searching program using the linking element to locate  
the set of selectable optional features and to integrate the set of selectable  
4 optional features with the main program to operate the wireless communication  
device.

20. The device of claim 17 wherein the set of selectable optional  
2 features includes a pointer to identify a memory location in the first or second

WO 00/54530

PCT/US00/06552

19

storage locations, the memory location programmable to store a one of the set  
4 of selectable optional features.

21. The device of claim 17 wherein the set of selectable optional  
2 features includes a secondary linking element, the secondary linking element  
having a plurality of pointers to identify a plurality of corresponding memory  
4 locations in the first or second storage locations, the corresponding memory  
locations programmable to store a one of the set of selectable optional features.

22. The device of claim 17 wherein the linking element is a portion of  
2 the main program stored in the first storage location.

23. The device of claim 17 wherein the set of selectable optional  
2 features includes one of a dialing plan system, encryption system, browser  
system, or language system.

24. A method for storing programs in a wireless communication  
2 device comprising:

storing a main program to operate the wireless communication device in  
4 a memory;

downloading a set of selectable optional features into the memory  
6 independently of the storing of the main program; and

dynamically linking the main program to the downloaded features to  
8 thereby locate any one of the downloaded features in the set of selectable  
optional features.

25. The method of claim 24, further comprising providing a link from  
2 the main program to the set of selectable optional features and keeping the link  
inactive until the downloading of the set of selectable optional features.

26. The method of claim 25 wherein the link has a plurality of  
2 pointers to identify a corresponding plurality of storage locations in the

WO 00/54530

PCT/US00/06552

20

memory, the downloading of the selectable optional features further  
4 comprising:  
reading one of the plurality of pointers to locate one of the plurality of  
6 storage locations;  
receiving any one of the set of selectable optional features into the one of  
8 a plurality of storage locations for storage; and  
setting an indicator to indicate that the any one of the set of selectable  
10 optional features has been stored in the one of a plurality of storage locations.

27. The method of claim 24 wherein the downloading of the set of  
2 selectable optional features occurs after storing the main program in the  
memory.

28. The method of claim 24, further comprising activating a pointer in  
2 the main program to identify a corresponding storage location in the memory  
to store the set of selectable optional features during the downloading.

29. The method of claim 24 wherein the downloading of the set of  
2 selectable optional features further comprises:  
locating an empty storage location in the memory to store the set of  
4 selectable optional features; and  
setting an indicator to indicate when the storing of the set of selectable  
6 optional features in the second storage location has occurred.

WO 00/54530

PCT/US00/06552

1/4




FIG. 1

WO 00/54530

PCT/US00/06552

2/4




FIG. 2



WO 00/54530

PCT/US00/06552

3/4




FIG. 3

WO 00/54530

PCT/US00/06552

4/4




FIG. 4

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/06552

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04Q7/32

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 16938 A (NOKIA TELECOMMUNICATIONS OY ;LEPPAENEN REIJO (FI)) 9 May 1997 (1997-05-09)  page 7, line 35 -page 8, line 26 page 9, line 32 -page 10, line 19 ---	1-3,5,6, 8-11,13, 15-18, 20,22, 24,25, 27,28
Y	WO 98 58506 A (ERICSSON TELEFON AB L M) 23 December 1998 (1998-12-23)  page 18, line 7 - line 11 --- -/--	8,12,14, 17,21, 24,26,29



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents :

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*G\* document member of the same patent family

Date of the actual completion of the international search

7 June 2000

Date of mailing of the international search report

03/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Bernedo Azpiri, P

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/06552

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	SUN MICROSYSTEMS: "Linker and Libraries Guide (part no. 802-6319)" 'Online! 1 August 1997 (1997-08-01) , SUN MICROSYSTEMS, INC. , MOUNTAIN VIEW, CA, USA XP002139367 page 209, line 22 -page 223, line 16 -----	8,12,14, 17,21, 24,26,29

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/06552

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
W0 9716938 A	09-05-1997	FI 955188 A	24-06-1997
		AU 6877696 A	22-05-1997
		EP 0872138 A	21-10-1998
		JP 11514760 T	14-12-1999
<hr/>			
W0 9858506 A	23-12-1998	SE 512110 C	24-01-2000
		AU 8049798 A	04-01-1999
		EP 0983697 A	08-03-2000
		NO 996246 A	14-02-2000
		SE 9702322 A	18-12-1998
<hr/>			

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**